



## **HARLEQUIN ROCKSURE CLEANING & MAINTENANCE**

### **ENTRANCE MATTING**

Entrance matting is an important aspect of maintaining the appearance and performance of your flooring. It serves as the first line of defense by significantly reducing the amount of wet and dry soiling that is brought in on footwear. For maximum effectiveness, it is recommended that the length of the matting be at least 2 to 3 feet and that it be regularly vacuumed and cleaned.

### **DAILY MAINTENANCE**

To maintain your flooring's appearance and performance, it is important to follow the recommended maintenance instructions. Daily maintenance should involve sweeping the floor with a soft broom or dust control mop to remove any loose dirt, debris, and dust. Then, damp mop the floor with a diluted solution of Harlequin Vinyl Daily Floor Cleaner in a ratio of 1:50, using 100 ml of daily floor cleaner in 5 liters of warm water. Rinse the floor with a damp, not wet mop and allow it to dry before use. Avoid saturation of the floor.

### **BEST PRACTICES**

In addition to daily maintenance, there are some best practices to keep in mind. Always protect newly installed floors by covering them when other trades are operating. Regular cleaning is more effective in retaining the performance of the product than occasional deep cleaning. The frequency and type of maintenance required depend on the frequency of use, degree of soiling, and hygiene standard required. Always use Harlequin's recommended floor cleaning products and follow the recommended dilution rates. Improper use can cause irreparable damage to the floor covering, including shrinkage and staining/discoloration. Avoid using abrasive powders/creams, strong solvents such as Acetone, or highly alkaline solutions. Additionally, the floor should not be exposed to any bare metal with sharp edges as it will damage the floor. Clean up any liquid spills as soon as possible.

Ideal ambient conditions are 50% RH (relative humidity) at a nominal temperature of 77° F. By following these guidelines, you can ensure that your flooring retains its appearance and performance for longer.

If you have any questions regarding the installation or maintenance of your Harlequin floor, please contact us at 800-642-6440.